SETON

Technical card

Flexibele, lage beschermbalk PARFLEX


306QRA100

306QRB100


306QRC100


306QRD100

Description

- End-of-radius barriers protect equipment (racks, etc.) warn vehicles of danger.
- The pubcode **306QRA100** and **306QRC100** have passed a stress test with a force of more than 10,000 Joules. This corresponds to 5,000 kg thrown at more than 7 km / h with an impact angle of 90 °.
- The pubcode **306QRB100** and **306QRD100** have been tested with a force of 2500 Joules, corresponding to 2000 kg launched at more than 5 km / h.
- Fixing material is included, Fischer ULTRACUT FBS II system.

Datasheet

- **Material :** Polyethylene, recyclability 100%.
- **CO2 / m³ :** 20 kg
- **Color :** Yellow (like RAL 1023 traffic yellow) / black.
- **To use :** indoor and outdoor.
- **Fixing :** floor fixing (8 boreholes, fixing material is included).
- **Temperature Range :** -10° up to + 50°.
- **Chemical Resistance :** high - ISO/TR 10358.
- **Warranty :** 5 years.

Ref.	Description	Width / Height	Weight
306QRA100	Rack single rail	L 1100 x H 516 mm	23,6 kg
306QRB100	Rack single rail	L 2500 x H 516 mm	26,2 kg
306QRC100	Rack double rail	L 1100 x H 760 mm	25,6 kg
306QRD100	Rack double rail	L 2500 x H 760 mm	28,6 kg